

BREAKER


TECHNISCH BUREAU

DUSPRA

KD 12

Breaker respects all safety CE norms and limits on noise, vibration level and defence against accidental starting

kg 14



Available in
underwater version



- *Anti vibration handle according to the newest CE regulations allows operators comfort and safety*
- *Can work at flow 20 or 30 L/min*
- *Only one dynamic seal and few moving parts to assure maximum reliability and a unbeatable operative longevity*
- *High tolerance to back pressure allows to use it with very long oil hoses*

KD12 hydraulic breaker Kg14 with “D type” anti vibration handle, the tool is “operator friendly” and its use is ideal in general demolition works either in vertical and horizontal position against walls. **KD12** gives the best compromise between high power and manoeuvrability, can be powered by power packs or by the hydraulic circuit of mini excavators, trucks or other machines with sufficient hydraulic circuit. The hydraulic functioning assures quietness, productivity, fuel economy united with the excellent transportability of the group power pack/ breaker eliminating the typical problems of transport and movements of the bulky air compressors and pneumatic breakers.

TECHNICAL CHARACTERISTICS	KD 12
Weight (kg)	14
Dimension LxP (cm)	60x19
Tool bitz size mm	22x82 std (7/8"x3 ^{3/4} ")
Flow L/min	20-30
Ideal flow L/min	20
Pressure Bar	140
Blow frequency	1300-1500
Impact energy	5,5 KGM
Handle type	“D” anti vibration



 **DOA**
Hydraulic Tools

B.V. Technisch Bureau Duspra Amersfoortseweg 24-14 3951 LB Maarn The Netherlands
Tel: +31(0)180-410100 E: sales@duspra.nl W: www.duspra.nl