



SPITZNAS
CUSTOMIZED POWER SOLUTIONS



PIPE CUTTING MACHINES

TOOLS FOR THE SPECIALIST

PNEUMATIC



HYDRAULIC



ATEX



SYSTEM CONCEPT



Tool holder



Air connection
with sensor block



Adjustment for the
cutting depth

ATEX-Safety class
approved



Guard



Pneumatic or hydraulic
drive unit



Cooling water
connection



PNEUMATIC DRIVE UNIT

The pneumatic drive unit with two gear steps for **cutting and bevelling** for pipes made of different material, as:

- Ductile iron
- Concrete
- Cement
- Clay
- Non-ferrous metal
- Plastics
- PE
- PVC
- GRP



ORDER NO.	ATEX Specification	Power	Air consumption	Blade dia. max.	Tool holder	OPER. PRESSURE		Cutting depth max.	Height	Noise level LpA	Vibration level	Weight
						6 Bar						
		kW	m ³ /min	mm	mm	rpm	rpm	mm	mm	dB(A)	m/s ²	kg
5 8002 7000	II2GExhIIBT6Gb	1.8	2.2	180	22.2/30.0	1,800	350	50	250	98	<2.5	13.0

Subject to technical change.

Performance data at an operating pressure of 6 bar.

PNEUMATIC DRIVE UNITS

The pneumatic drive unit with high torque for **cutting steel pipes** can be used as well for:

- Steel
- Stainless steel
- PE
- Concrete
- Cement
- Non-ferrous metal
- Plastics
- Ductile iron
- PVC
- GRP
- Clay



ORDER NO.	ATEX Specification	Power	Air consumption	Blade dia. max.	Tool holder	OPER. PRESSURE		Cutting depth max.	Height	Noise level LpA	Vibration level	Weight
						6 Bar						
		kW	m ³ /min	mm	mm	rpm	rpm	mm	mm	dB(A)	m/s ²	kg
5 8010 0050	II2GExhIIBT6Gb	2.4	3.0	180	22.2/30.0	1,800		50	250	98	<2,5	12.5
5 8011 0050	IM2ExhIMbT6	2.4	3.0	180	22.2/30.0	1,800		50	250	98	<2,5	17.5

Subject to technical change.

Performance data at an operating pressure of 6 bar.

HYDRAULIC DRIVE UNITS

The hydraulic unit with two gear steps/stepless adjusting for **cutting or bevelling** pipes of the following materials:

- Steel
- Stainless steel
- PE
- Concrete
- Cement
- Non-ferrous metal
- Plastics
- Ductile iron
- PVC
- GRP
- Clay



ORDER NO.	ATEX Specification	Power	Volume flow	Blade dia. max.	Tool holder	OPER. PRESSURE		Cutting depth max.	Height	Noise level LpA	Vibration level	Weight
						90-140 bar ¹⁾ /140-180 bar ²⁾						
		kW	l/min	mm	mm	rpm	rpm	mm	mm	dB(A)	m/s ²	kg
5 8006 7000¹⁾	II2GExhIIBT6Gb	2.0	15-50	180	22.2/30.0	950	200	50	250	98	<2.5	13.0
5 8016 0050²⁾	II2GExhIIBT5Gb	2.3	20-23	180	22.2/30.0	0-1,050*		50	250	98	<2.5	14.9

Subject to technical change.

²⁾steplessly adjustable

Performance data at an operating pressure of 90¹⁾ bar/140²⁾ bar.


TECHNICAL DATA

SYSTEM ACCESSORIES

ASSEMBLY PARTS


Just specify your individual application and we custom-assemble your pipe cutting machine with the required accessories.

Pipe dia. / ORDER NO. [mm]	Guide carriage small	Guide carriage large	Chain tensioner	Tensioning chain	Guide chain
300-400	1 x 5 8010 8090		1 x 5 8003 8300		1 x 5 8002 8760
400-800	1 x 5 8010 8090	1 x 5 8010 8100	1 x 5 8002 8400	1 x 5 8002 8710	1 x 5 8002 8780
600-900		2 x 5 8010 8100	2 x 5 8002 8400		1 x 5 8002 8810
400-1400	1 x 5 8010 8090	2 x 5 8010 8100	2 x 5 8002 8400	1 x 5 8002 8710	1 x 5 8002 8820
400-1600	2 x 5 8010 8090	2 x 5 8010 8100	2 x 5 8002 8400	2 x 5 8002 8710	1 x 5 8002 8830



GUIDE CARRIAGES

ORDER NO.	Pos.	Description
5 8010 8090	1	Guide carriage small (aluminium)
5 8011 8090	1	Guide carriage small (zamak)
5 8010 8100	2	Guide carriage large (aluminium)
5 8011 8100	2	Guide carriage (zamak)



GUIDE CHAINS

ORDER NO.	Description	For pipe dia. [mm]
5 8002 8760	Guide chain including tightener and 24 chain links	≤ 400
5 8002 8770	Guide chain including tightener and 35 chain links	≤ 600
5 8002 8780	Guide chain including tightener and 46 chain links	≤ 800
5 8002 8810	Guide chain including tightener and 57 chain links	≤ 1000
5 8002 8790	Guide chain including tightener and 68 chain links	≤ 1200
5 8002 8820	Guide chain including tightener and 79 chain links	≤ 1400
5 8002 8830	Guide chain including tightener and 90 chain links	≤ 1600




TIGHTENER

ORDER NO.	Description
5 8002 6800	Tightener



CHAIN LINKS

ORDER NO.	Pos.	Description
5 8001 8750	1	Chain link, length 57 mm
5 8001 8760	2	Chain link, length 57 mm, with magnet
5 8001 8860	3	Chain link set (set of 5 pieces, preassembled)
5 8001 8960	3	Chain link set (set of 6 pieces, preassembled), with magnet



SYSTEM ACCESSORIES

SYSTEM ACCESSORIES


TENSIONING CHAIN

ORDER NO.	Description
5 8002 8710	Tensioning chain, length 950 mm




CHAIN TENSIONERS FOR TENSIONING CHAIN

ORDER NO.	Pos.	Description
5 8003 8300	1	Chain tensioner small
9 4902 0100	2	Chain lock for chain tensioner small for type 5 8003 8300
5 8002 8400	3	Chain tensioner large



FEEDING PIPES

ORDER NO.	Pos.	Description
5 8002 9500	1	Feeding pipe
5 8010 9500	2	Feeding pipe, angled at 90° for narrow spaces



TOOL SET

ORDER NO.	Description
5 8002 9200	Tool set



CARRYING CASE

ORDER NO.	Description
5 8002 9300	Metal carrying case with trays



CARBIDE-TIPPED BLADES

ORDER NO.	Disc dia. [mm]	Center dia. [mm]	Cutting depth max. [mm]	For cutting
9 2503 0090	160	30.0	40	Steel, stainless steel from 4 mm wall thickness, plastics, PE, PVC
9 2503 0120	180	30.0	50	
9 2503 0130	200	30.0	60	



DIAMOND BLADES

ORDER NO.	Disc dia. [mm]	Center dia. [mm]	Cutting depth max. [mm]	For cutting
9 2503 0050	150	22.2	35	Cast iron, ductuile iron, concrete, cement, clay, GRP
9 2503 0100	180	22.2	50	



BEVELLING CUTTERS

ORDER NO.	Cutter dia. [mm]	Type	For bevelling of	For type
9 2530 7040	100	Cutter 45°	Steel, plastics, PE, PVC	5 8002, 5 8006, 5 8016
9 2530 7060	100	Cutter 60°		
9 2530 7090	100	Cutter 90°		



ADAPTERS FOR BLADES

ORDER NO.	Pos.	Description	Center dia. [mm]
5 8010 9720	1	Adapter complete	30.0
5 8002 8020	2	Adapter ring	22.2/30.0




SYSTEM ACCESSORIES

SYSTEM ACCESSORIES

SERVICE UNITS

ORDER NO.	Pos.	Description
9 2406 0260	1	Portable service unit with pressure regulator 3/4"
9 2406 0650	2	Portable service unit with protection housing and pressure regulator 3/4"



WATER TANK

ORDER NO.	Description
5 8002 9100	Water tank 10 l



MULTI-OIL SPRAY

ORDER NO.	Description
9 9902 0120	Multi oil for cleaning and protection



More accessories on request.

SAW RANGE

BAND SAWS



SABRE SAWS



CHAIN SAWS



RECIPROCATING SAWS



CIRCULAR SAWS



PIPE CUTTING MACHINES



0220E1

TECHNISCH BUREAU
DUSPRA

B.V. Technisch Bureau Duspra
Amersfoortseweg 24 - 14
3951 LB Maarn
The Netherlands

T: +31 (0)180 410 100
F: +31 (0)180 487 630
E: sales@duspra.nl
W: www.duspra.nl