

SAW BLADES

Other lengths on request.

All SPITZNAS saw blades cut on backward stroke.
Length of blade = Operating length + 130 mm.



Order no.

Teeth per inch
Length (mm)
Width (mm)
Height (mm)
Quality

						Plastic	GFK-Pipe	Hardboard	Asbestos cement	Concrete reinforced	Clinker	Aluminium (solid material)	Cast iron	Ductile iron (cement coated iron)	Tar coated cast iron pipe	Steel (solid material)	Reinforcing bar	Non-ferrous metal (non-precious)	Non-ferrous metal (precious)	Stainless steel	Rust-resistant steel	High stress steel (< 600 N/mm ²)
HSS																						
9 2501 0050	6	200	25	1.5	☆☆☆	x			x			x										
9 2501 0120	6	300	25	1.5	☆☆☆	x			x			x										
9 2501 0190	6	400	25	1.5	☆☆☆	x			x			x										
9 2501 0230	6	500	28	2.0	☆☆☆	x			x			x										
9 2501 0470	6	600	28	2.0	☆☆☆	x			x			x										
9 2501 0310	6	770	28	2.0	☆☆☆	x			x			x										
9 2501 0630	8	200	25	1.5	☆☆☆	x		x					x			x			x			
9 2501 0660	8	400	25	1.5	☆☆☆	x		x					x			x			x			
9 2501 0710	8	600	28	2.0	☆☆☆	x		x					x			x			x			
9 2501 0440	12	200	28	2.0	☆☆☆	x		x					x			x			x			
9 2501 0130	12	300	25	1.5	☆☆☆	x		x					x			x			x			
9 2501 0200	12	400	25	1.5	☆☆☆	x		x					x			x			x			
9 2501 0450	12	500	28	2.0	☆☆☆	x		x					x			x			x			
9 2501 0670	12	530	28	2.0	☆☆☆	x		x					x			x			x			
9 2501 0720	12	770	28	2.0	☆☆☆	x		x					x			x			x			
9 2501 0690	12	940	28	2.0	☆☆☆	x		x					x			x			x			
9 2501 0020	14	150	25	1.5	☆☆☆													x			x	x
9 2501 0060	14	200	25	1.5	☆☆☆													x			x	x
9 2501 0070	14	250	25	1.5	☆☆☆													x			x	x
9 2501 0140	14	300	25	1.5	☆☆☆													x			x	x
9 2501 0210	14	400	25	1.5	☆☆☆													x			x	x
9 2501 0240	14	500	28	2.0	☆☆☆													x			x	x
9 2501 0460	14	600	28	2.0	☆☆☆													x			x	x
9 2501 0300	14	770	28	2.0	☆☆☆													x			x	x
9 2501 0640	16	200	25	1.5	☆☆☆													x			x	x
9 2501 0610	16	300	25	1.5	☆☆☆													x			x	x
9 2501 0620	16	400	25	1.5	☆☆☆													x			x	x
HSS-SL																						
9 2501 0680	12	530	28	2.0	☆☆☆	x		x					x			x			x	x		x
9 2501 0730	12	770	28	2.0	☆☆☆	x		x					x			x			x	x		x
9 2501 0320	16	150	25	1.5	☆☆☆													x			x	x
9 2501 0330	16	200	25	1.5	☆☆☆													x			x	x
9 2501 0340	16	250	25	1.5	☆☆☆													x			x	x
9 2501 0350	16	300	25	1.5	☆☆☆													x			x	x
9 2501 0600	16	350	25	1.5	☆☆☆													x			x	x
9 2501 0360	16	400	25	1.5	☆☆☆													x			x	x
9 2501 0370	16	500	28	2.0	☆☆☆													x			x	x
9 2501 0380	16	770	28	2.0	☆☆☆													x			x	x
CARBIDE COATED-SL																						
9 2504 0500	-	300	25	2.0	☆☆☆								x	x	x							
9 2504 0510	-	400	25	2.0	☆☆☆								x	x	x							
9 2504 0520	-	500	28	2.0	☆☆☆								x	x	x							
9 2504 0530	-	600	28	2.0	☆☆☆								x	x	x							
9 2504 0540	-	700	28	2.0	☆☆☆								x	x	x							
9 2504 0550	-	770	28	2.0	☆☆☆								x	x	x							
CARBIDE TIPPED																						
9 2504 0610	4	300	50	-	☆☆☆		x			x	x		x	x	x							
9 2504 0620	4	400	50	-	☆☆☆		x			x	x		x	x	x							
9 2504 0630	4	500	50	-	☆☆☆		x			x	x		x	x	x							
9 2504 0640	4	600	50	-	☆☆☆		x			x	x		x	x	x							
9 2504 0650	4	770	50	-	☆☆☆		x			x	x		x	x	x							

Quality class : ☆☆☆ standard

☆☆☆ high quality

☆☆☆ highest quality

TECHNISCH BUREAU

DUSPRA

bv technisch bureau Duspra-Amersfoortseweg 24-14 - NL 3951 LB Maarn

Tel: +31(0)180-410100

Email: sales@duspra.nl

Fax: +31(0)180-487630

Internet: www.duspra.nl