



Rechargeable worklight

UltraXL



- Sewages and tunnels
- Aircraft building and maintenance
- Painting



# Rechargeable UltraXL

**Saving from day 1:** No transformer, cable or plugs needed: oneperson carries all. No on-site electrician needed.

- ✓ Work light with wide beam
- ✓ Operating time 12 hours at full power
- ✓ 3200 lumen
- ✓ Only 6 kg
- ✓ Maintenance free batteries









#### **History**

The *UltraXL* is a further development of the Ultra2. The Ultra2 was developed for Necplus by Artidor and came onto the market in 2017. The Ultra2 was the only ATEX rechargeable flood light with continuous 3200 lumens for eight hours. This combined with the incredible low weight of 5.6 kg made the lamp the only tool to illuminate difficult to reach places. In 2023 Necplus merged with Atexindustries, while the *UltraXL* was being developed. The main difference: continuous 3200 lumens for twelve hours.

ch Bureau Duspra Amersfoortseweg 24-14 3951 LB Maarn The Netherlands Tel: +31(0)180-410100 E: sales@duspra.nl W: www.duspra.nl

## **Accessories**



### Magnet set

For easy placing the UltraXL to a wall, beam, sheet or other magnetic object, use this solution. Three strong magnets connected to a stainless steel frame. The magnets are covered to avoid sparking and are flexibly connected to the frame to adjust automatically to curved, bumpy or rusty surfaces.



### **Scaffolding hook**

To secure the UltraXL on a horizontal bar.



## Leather Pouch

Keeps hands free thanks to this carrying pouch. Use the custom made leather pouch on your shoulder. Full grain leather of 2.5 mm. Including leather strap. Buckles and metal parts in stainless steel. Side pocket for charger.



### **Subframe and Tripod**

To position the light towards any object. Tilts the lamp up to 270°. Easy adjustment through one knob.

To be combined with the tripod. Height adjustable from 1,38 meter to 2,50 meter.



## Shockproof case

Carry all you need in this shockproof case.



## Specifications UltraXL

## **Partnumbers**

Watts	23W
Source	81 LEDs, 5000°K
Lumen	3200
Operating time	12 h
Chargetime	up to 12 h.
Battery	Lithium Polymer (LiPo) 260Wh
Composition	Throughout antistatique polypropylene, metal frame, stainless steel bolts
Lens materials	Scratch and chemical resistant hardened glass with safety and diffusor foil
Design	By design easy to handle, also with gloves on. By design easy stackable to save space.
Dimensions	388 x 319 x 147 mm
Weight	Only 6 kg
Ingress protection level	IP65 according to EN 60529
Product category	2
Ex-marking gas	II 2 G Ex eb ib IIC T4 Gb
Ex-marking dust	II 2 D Ex ib tb IIIC T135°C Db
Zones	1, 2, 21 and 22
Ambient temperature	-20°C to +45°C
Eye safety	Complies with photobiologicalsafety as defined in the IEC 62471 standard
Conformity	2014/34/EU (ATEX) 2014/30/EU (EMC)
Applicable standards	EN 60079-0:2018 EN 60079-7:2015 + A1:2018 EN 60079-11:2023 EN 60079-31:2014
Charger	Floodlight supplied with charger. It includes a number of attachments that can be used in all European wall sockets.
Supply voltage charger	100 to 240 VAC, 50/60 Hz
Charging	Charging only in safe area

Product number OltraxL	
536062400	
Partnumbe	ers Accessories
536920357	Magnetset. Three spark free magnets on bracket.
536921003	Antistatic protective film
536960430	Stainless steel sub frame
536960516	Stainless steel tripod
536960420	Stainless steel scaffolding hook with locking device
536960440	Leather satchel for handsfree carrying
536960450	High end transportation case of copolymer

Please contact with your dealer:

Product number I Iltra XI



**www.duspra.nl** +31 (0) 180 410 100 | sales@duspra.nl

Data and pictures approximately only. Can be changed without prior notice.