## Hi-Force

## HIGH PRESSURE HYDRAULIC HOSES - BLACK & RED



Hi-Force high pressure hydraulic hoses provide the vital, high quality, safe connection for your hydraulic equipment. Available in black and red and supplied complete with an ergonomically designed protective strain reliever at both ends, Hi-Force high pressure hoses are suitable for working pressures up to 700 Bar with a 4 : 1 factor of safety.

Working pressure 700 Bar

4:1 Factor of safety

Hand grip protective strain relievers



Tip for double acting systems ...

By using black hoses for the advance lines and red hoses for the retract lines, identification is made easy and the possibility of incorrectly connected hoses is reduced.

## Red Black Black Black Red Red <sup>3</sup>/<sub>8</sub>" - 18 NPT male fitting No couplers <sup>3</sup>/<sub>8</sub>"- 18 NPT male one end with CM1 coupler CM1 male couplers fitted both ends fittings both ends fitted one end Model number Model number Model number **HH0.5** HC0.5C HH0.5R **HCO.5** HCO.5R HCO.5CR HH1 HC1 HC1R HC1C HH1R HC1CR HH2R HC2R HH2 HC2 HC2C HC2CR HH3 **HH3R** HC3 **HC3R** HC3C HC3CR

HC4R

HC5R

HC6R

HC10R

HC12R

HC15R

HC20R

HC25R

HC30R

## Hose bore is 6.6mm and outside diameter is 12.7mm

HC4C

HC5C

HC6C

HC10C

HC12C

HC15C

HC20C

**HC25C** 

HC30C

HC4CR

HC5CR

**HC6CR** 

HC10CR

HC12CR

HC15CR

HC20CR

HC25CR

HC30CR

B.V.Technisch Bureau Duspra Amersfoortseweg 24-14 3951 LB Maarn The Netherlands Tel: +31(0)180-410100 E: sales@duspra.nl W: www.duspra.nl

HC4

HC5

HC6

**HC10** 

HC12

HC15

**HC20** 

**HC25** 

HC30

Length

Metres 0.5

1.0

2.0

3.0

4.0

5.0

6.0

10.0

12.0

15.0

20.0

25.0

30.0

HH4

HH5

HH6

**HH10** 

**HH12** 

**HH15** 

**HH20** 

**HH25** 

**HH30** 

HH4R

HH5R

HH6R

HH10R

HH12R

**HH15R** 

HH2OR

HH25R

HH30R